

MEDIUM PRESSURE BOOSTER COMPRESSOR CB 10-40 BAR 2 stages



* Frame type:
- version C: Cabinet frame
- version M: Silenced frame, suitable for outdoor installation.

BASIC VERSION								
Model	F.A.D.		Phase	Frame type*	Weight		Dimensions L x W x H	Price EUR
	l/min 10 bar	l/min 40 bar			Kg	lbr		
CB44072809 2,2 kW	123	109	three	C	228	502	75 x 93 x 123	€ 15.380,00
				M	258	568	75 x 108 x 134	€ 16.720,00
CB44082809 2,5 kW	188	162	three	C	230	507	75 x 93 x 123	€ 16.290,00
				M	260	573	75 x 108 x 134	€ 17.630,00
CB44082812 2,8 kW	255	220	three	C	230	507	75 x 93 x 123	€ 17.180,00
				M	260	573	75 x 108 x 134	€ 18.520,00
CB44082815 3 kW	310	267	three	C	233	513	75 x 93 x 123	€ 18.100,00
				M	263	579	75 x 108 x 134	€ 19.440,00
CB44093215 5 kW	370	329	three	C	233	513	75 x 93 x 123	€ 18.990,00
				M	263	579	75 x 108 x 134	€ 20.330,00
CB45113209 7 kW	450	396	three	C	241	531	75 x 93 x 123	€ 21.450,00
				M	271	597	75 x 108 x 134	€ 22.790,00
CB45113212 8 kW	553	500	three	C	251	553	75 x 93 x 123	€ 22.460,00
				M	281	619	75 x 108 x 134	€ 23.800,00
CB45113215 9 kW	690	635	three	C	251	553	75 x 93 x 123	€ 23.240,00
				M	281	619	75 x 108 x 134	€ 24.580,00

In case of order please specify :

- Operating pressure : Max pressure 40 bar/580 psi
- Operating voltage: 3-Phase: 230V/50Hz - 230V/60Hz - 400V/50Hz - 400V/60Hz - 440V/50Hz - 440V/60Hz - 480V/50Hz - 480V/60Hz

In case this information is not provided, the price will be calculated with standard configuration

OPTIONAL EQUIPMENT	Price EUR
Oil Pump Lubrication and Electric control panel	INCLUDED
Soft Start	1.400,00
Suction Filter 50 micron G1" – PA002-198	198,00
ATEX CERTIFICATE ZONE II	4.875,00

All prices are quoted in euros EX-WORKS (Incoterms ICC 2020).