

MEDIUM PRESSURE AIR/NITROGEN BOOSTER BM 40-60 BAR 1 stage



* Frame type:

- version E: Open frame

- version C: Cabinet frame

- version M: Silenced frame, suitable for outdoor installation.

BASIC VERSION

Model	F.A.D.		Phase	Frame type*	Weight		Dimensions L x W x H	Price EUR
	l/min 4 bar	l/min 12 bar			Kg	lbr		
BM642807 3,5 kW	220	670	three	E	102	224	103 x 53 x 65	€ 12.320,00
				C	228	502	75 x 93 x 123	€ 16.250,00
				M	258	568	75 x 108 x 134	€ 17.590,00
BM642810 4,5 kW	310	930	three	E	104	229	103 x 53 x 65	€ 13.230,00
				C	230	507	75 x 93 x 123	€ 17.160,00
				M	260	573	75 x 108 x 134	€ 18.500,00
BM643210 5,5 kW	405	1215	three	E	104	229	103 x 53 x 65	€ 14.160,00
				C	230	507	75 x 93 x 123	€ 18.090,00
				M	260	573	75 x 108 x 134	€ 19.430,00
BM643610 6,5 kW	515	1540	three	E	112	246	103 x 53 x 65	€ 15.100,00
				C	233	513	75 x 93 x 123	€ 19.030,00
				M	263	579	75 x 108 x 134	€ 20.370,00
BM643613 7,5 kW	660	1980	three	E	112	246	103 x 53 x 65	€ 15.970,00
				C	233	513	75 x 93 x 123	€ 19.900,00
				M	263	579	75 x 108 x 134	€ 21.240,00
BM653213 8 kW	710	2150	three	C	251	553	75 x 93 x 123	€ 23.550,00
				M	281	619	75 x 108 x 134	€ 24.890,00
BM653613 12 kW	900	2700	three	C	251	553	75 x 93 x 123	€ 25.100,00
				M	281	619	75 x 108 x 134	€ 26.440,00

In case of order please specify :

- Operating pressure : Max pressure 60 bar/870 psi
- Operating voltage: 3-Phase: 230V/50Hz - 230V/60Hz - 400V/50Hz - 400V/60Hz - 440V/50Hz - 440V/60Hz - 480V/50Hz - 480V/60Hz

In case this information is not provided, the price will be calculated with standard configuration

OPTIONAL EQUIPMENT	Price EUR
Oil Pump Lubrication	INCLUDED
Electric control panel	INCLUDED
Soft Start (included for 12 Kw)	1400,00
Suction Filter 50 micron G1" – PA001-219	198,00

All prices are quoted in euros EX-WORKS (Incoterms ICC 2020).