

# ATLANTIC P60 - P100 – G100

max 330 Bar / 4700 psig

4 stages



BASIC VERSION										
Model	F.A.D.		Speed rpm	Power kW	Phase	Purification system	Weight		Dimensions L x W x H	Price EUR
	l/min	cfm					Kg	lbr		
Electric engine										
ATLANTIC P 60/1	60	2,1	2100	1,5	single	ATL	39,5	87,1	58 x 41 x 41	3.800,00
ATLANTIC P 100/1	100	3,5	2100	2,2	single	ATL	42,5	92,6	58 x 41 x 41	3.800,00
ATLANTIC P 100/3	100	3,5	2100	3,0	three	ATL	42	92,6	58 x 41 x 41	3.800,00
Gasoline engine										
ATLANTIC G 100	100	3,5	2100	4,2	-	ATL	42	92,6	77 x 41 x 41	3.965,00

**NOTE: Hour meter, maintaining valve and no-return valve on the filter are included as standard features.**

According to directive DIN EN 12021

In case of order please specify :

- Operating pressure : 225 bar/3200 psi or 330 bar/4700 psi
- Connection type only for 225 bar/3200 psi : DIN or INT (YOKE) or DIN with reduction INT (YOKE).  
Length of all filling hoses = 1meter
- Operating voltage (electric version single phase) Volt/Hz : 230/50 – 230/60
- Operating voltage (electric version three phase) Volt/Hz : 230/50 - 230/60 - 400/50 - 400/60 - 440/50 - 440/60

In case this information is not provided, the price will be calculated with standard configuration

OPTIONAL EQUIPMENT	Price EUR
Reduction connection DIN / INT-YOKE only for 225 bar/3200psi with connection DIN	€ 45,50
Filling hose holder	€ 32,50
Additional hose connections (for a maximum of 2 hose connections : 225bar/3200 or 330bar/4700psi)	€ 293,00
Double pressure with safety valve(2 hose connections : n°1 225bar/3200 psi and n°1 330bar/4700psi)	€ 293,00
Double pressure with pressure reducer (2 hose connections : n°1 225bar/3200 psi and n°1 330bar/4700psi)	€ 1.037,00
Final pressure switch with automatic-stop	€ 285,00
Trolley (2 wheels and handle)	€ 293,00
Folding trolley (2 wheels and reclining handle)	€ 841,00
Automatic condensate drain ATLANTIC P (For electric model with single phase motors)	€ 407,00
Automatic condensate drain ATLANTIC G (For Gasoline model and electric 3-phase model)	€ 537,00
Double purification system	€ 660,00
Eco-friendly Condensate Collecting Container/Tank 5L.	€ 130,00

All prices are quoted in euros EX-WORKS (Incoterms ICC 2020).



## **ATLANTIC D100**

**max 330 Bar / 4700 psig**



BASIC VERSION										
Model	F.A.D.*		Speed rpm	Power kW	Phase	Purification system	Weight		Dimensions L x W x H	Price EUR
	l/min	cfm					Kg	lbr		
Diesel engine										
ATLANTIC D 100	100	3,5	2100	3,5	-	ATL	61	135	82 x 37 x 50	6.500,00

**NOTE: Hour meter, maintaining valve and no-return valve on the filter are included as standard features.**

\* Filling rate for 10 liter cylinder capacity from 0 to 200 bar  $\pm 5\%$

\*\* According to directive DIN EN 12021

In case of order please specify :

- Operating pressure : 225 bar/3200 psi<sup>(1)</sup> or 330 bar/4700 psi
- Connection type only for 225 bar/3200 psi : DIN<sup>(1)</sup> or INT (YOKE) or DIN with reduction INT (YOKE).  
All filling hoses in length of 1 m.

(1) In case this information is not provided, the price will be calculated with standard configuration

<b>OPTIONAL EQUIPMENT</b>	<b>Price</b> <b>EUR</b>
Reduction connection DIN / INT-YOKE only for 225 bar/3200psi with connection DIN	€ 45,50
Additional hose connections (for a maximum of 2 hose connections : 225bar/3200 or 330bar/4700psi)	€ 293,00
Double pressure with safety valve(2 hose connections : n°1 225bar/3200 psi and n°1 330bar/4700psi)	€ 293,00
Double pressure with pressure reducer (2 hose connections : n°1 225bar/3200 psi and n°1 330bar/4700psi)	€ 1.037,00

All prices are quoted in euros EX-WORKS (Incoterms ICC 2020).



**Price list**  
**HIGH PRESSURE**  
**BREATHING AIR COMPRESSOR**

**PL BREATHING HP-23**

**rev.00**

**pag. 3 di 11**

## PACIFIC E - EG

**max 330 Bar / 4700 psig**



BASIC VERSION											
Model	F.A.D.		Nr. of stages	Speed rpm	Power kW	Phase	Purification system	Weight		Dimensions L x W x H	Price EUR
	l/min	cfm						Kg	lbr		
Electric motor											
PACIFIC E 16 * <i>(not available with Control Panel)</i>	160	5,6	3	1350	3,0	single	PAC 1	108	238	103 x 53 x 65	8.345,00
PACIFIC E 23 *	230	8,1	3	1350	4,0	three	PAC 1	108	238	103 x 53 x 65	8.425,00
PACIFIC E 27 *	270	9,5	3	1550	5,5	three	PAC 1	118	260	103 x 53 x 65	9.220,00
PACIFIC E 30	300	10,6	3	1450	5,5	three	PAC 1	118	260	103 x 53 x 65	10.255,00
PACIFIC E 35	350	12,4	4	1550	7,5	three	PAC 1	123	277	103 x 53 x 65	12.275,00
Gasoline engine											
PACIFIC EG 23 *	230	8,1	3	1350	6,7	-	PAC 1	108	238	111 x 53 x 65	9.410,00
PACIFIC EG 27 *	270	9,5	3	1550	6,7	-	PAC 1	108	238	111 x 53 x 65	10.670,00
PACIFIC EG 30	300	10,6	3	1450	10	-	PAC 1	118	260	111 x 53 x 65	11.795,00
PACIFIC EG 35	350	12,4	4	1550	10	-	PAC 1	123	277	111 x 53 x 65	14.390,00

\* With splash lubrication , Oil pump is optional

According to directive DIN EN 12021

In case of order please specify :

- Operating pressure : 225 bar/3200 psi or 330 bar/4700 psi (standard version supplied with 2 filling devices)  
Connection Type only for 225 bar/3200 psi : DIN or INT (YOKE) or DIN with reduction INT (YOKE). Length of all filling hoses = 1meter
- Operating voltage (electric version single phase) Volt/Hz : 230/50<sup>(1)</sup> - 230/60
- Operating voltage (electric version three phase) Volt/Hz : 230/50 - 230/60 - 400/50 - 400/60 - 440/50 - 440/60 - 480/50 - 480/60

In case this information is not provided, the price will be calculated with standard configuration

OPTIONAL EQUIPMENT	Price /EUR
Oil Pump Lubrication (Only for models indicated with an asterisk *)	€ 615,00
Automatic System for Electric models (Elect. Control Panel and Automatic Condensate Drain)	€ 2.470,00
Soft Start (available for PACIFIC E with charging rate 230 lpm, 270 lpm, 300 lpm and 350 lpm)	€ 1.398,00
Oil Alert	€ 260,00
Additional Pressure Sensors (only for Electric models) (unit price per sensor)	€ 430,00
Additional Temperature Sensors (only for Electric models) (unit price per sensor)	€ 170,00
Hour Meter (Only for Gasoline models and electrical with manual controls)	€ 178,00
Filtering System (PAC Filter 2)	€ 375,00
Filtering System (PAC Filter 3) Upgrade from PAC Filter 1	€ 765,00
Filtering System (PAC Filter 3) Upgrade from PAC Filter 2	€ 390,00
Double pressure (Pressure reducer with 2 ea. Filling devices 2-fold with 2 connections at 225bar/3200psi and 2 connections at 330bar/4700psi – Standard version supplied with 1 filling hose DIN 200 bar and 1 filling hose DIN 300 bar)	€ 894,00
Filling device 4-fold (supplied with 2 filling connections and 2 plugs either at DIN 200, 225bar/3200psi or DIN 300, 330bar/4700psi)	€ 275,00
Additional hose connections (for a maximum of 2 hose connections : 225bar/3200 or 330bar/4700psi)	€ 260,00
Reduction connection DIN / INT-YOKE only for 225 bar/3200psi with connection DIN (each piece)	€ 47,00
Trolley (2 wheels and handle)	€ 455,00
Handles (Set of 2)	€ 252,00
Eco-Friendly Condensate Collecting Container/Tank 12 l.	€ 130,00
Large separators	€ 260,00

All prices are quoted in euros EX-WORKS (Incoterms ICC 2020).



**Price list**  
**HIGH PRESSURE**  
**BREATHING AIR COMPRESSOR**

**PL BREATHING HP-23**

**rev.00**

**pag. 4 di 11**



## PACIFIC P - PG

**max 330 Bar / 4700 psig**



BASIC VERSION											
Model	F.A.D.		Nr. of stages	Speed rpm	Power kW	Phase	Purification system	Weight		Dimensions L x W x H	Price EUR
	l/min	cfm						Kg	lbr		
Electric motor											
PACIFIC P 16 *	160	5,6	3	1350	3,0	single	PAC 1	127	300	120 x 54 x 67	9.285,00
PACIFIC P 23 *	230	8,1	3	1350	4,0	three	PAC 1	127	300	120 x 54 x 67	9.285,00
PACIFIC P 27 *	270	9,5	3	1550	5,5	three	PAC 1	137	302	120 x 54 x 67	10.325,00
PACIFIC P 30	300	10,6	3	1450	5,5	three	PAC 1	137	302	120 x 54 x 67	11.490,00
PACIFIC P 35	350	12,4	4	1550	7,5	three	PAC 1	142	313	120 x 54 x 67	13.375,00
Gasoline engine											
PACIFIC PG 23 *	230	8,1	3	1350	6,7	-	PAC 1	113	249	120 x 54 x 67	10.775,00
PACIFIC PG 27 *	270	9,5	3	1550	6,7	-	PAC 1	113	249	120 x 54 x 67	11.325,00
PACIFIC PG 30	300	10,6	3	1450	10	-	PAC 1	123	271	120 x 54 x 67	12.515,00
PACIFIC PG 35	350	12,4	4	1550	10	-	PAC 1	128	282	120 x 54 x 67	14.985,00

\* With splash lubrication , Oil pump is optional

According to directive DIN EN 12021

In case of order please specify :

- Operating pressure : 225 bar/3200 psi or 330 bar/4700 psi (standard version supplied with filling device 4-fold with 2 hose connections)
- Connection Type only for 225 bar/3200 psi : DIN or INT (YOKE) or DIN with reduction INT (YOKE). Length of all filling hoses = 1meter
- Operating voltage (electric version single phase) Volt/Hz : 230/50<sup>(1)</sup> - 230/60
- Operating voltage (electric version three phase) Volt/Hz : 230/50 - 230/60 - 400/50 - 400/60 - 440/50 - 440/60 - 480/50 - 480/60

In case this information is not provided, the price will be calculated with standard configuration

OPTIONAL EQUIPMENT										Price/EUR
Oil Pump Lubrication (Only for models indicated with an asterisk *)										€ 615,00
Automatic System for Electric models (Elect. Control Panel and Automatic Condensate Drain)										€ 2.360,00
Automatic System for Gasoline models (Auto. Cond. Drain, Autostop, Electric Start with Key)										€ 2.275,00
Soft Start (available for PACIFIC P with charging rate 230 lpm, 270 lpm, 300 lpm and 350 lpm)										€ 1.398,00
Oil Alert										€ 260,00
Additional Pressure Sensors (only for Electric models) (unit price per sensor)										€ 430,00
Additional Temperature Sensors (only for Electric models) (unit price per sensor)										€ 170,00
Hour Meter (Only for Gasoline models and electrical with manual controls)										€ 178,00
Filtering System (PAC Filter 2)										€ 375,00
Filtering System (PAC Filter 3) Upgrade from PAC Filter 1										€ 765,00
Filtering System (PAC Filter 3) Upgrade from PAC Filter 2										€ 390,00
Double pressure (Pressure reducer with 2 ea. Filling devices 2-fold with 2 connections at 225bar/3200psi and 2 connections at 330bar/4700psi – Standard version supplied with 1 filling hose DIN 200 bar and 1 filling hose DIN 300 bar)										€ 894,00
Additional hose connections (for a maximum of 2 hose connections : 225bar/3200 or 330bar/4700psi)										€ 260,00
Reduction connection DIN / INT-YOKE only for 225 bar/3200psi with connection DIN (each piece)										€ 47,00
Trolley (2 wheels and handle)										€ 455,00
Handles (Set of 2)										€ 252,00
Eco-Friendly Condensate Collecting Container/Tank 12 l.										€ 155,00
Large separators										€ 260,00

All prices are quoted in euros EX-WORKS (Incoterms ICC 2020).



## PACIFIC DY

**max 330 Bar / 4700 psig**



BASIC VERSION											
Model	F.A.D.		Nr. of stages	Speed Rpm	Power kW	Engine	Purification system	Weight		Dimensions L x W x H	Price EUR
	l/min	cfm						Kg	lbr		
Diesel Engine											
PACIFIC DY 23 *	230	8,1	3	1350	7,4	Yanmar	PAC 1	165	364	109 x 58 x 65	15.405,00
PACIFIC DY 27 *	270	9,5	3	1550	7,4	Yanmar	PAC 1	165	364	109 x 58 x 65	16.215,00
PACIFIC DY 30	300	10,6	3	1450	7,4	Yanmar	PAC 1	172	379	109 x 58 x 65	17.340,00
PACIFIC DY 35	320	12,7	4	1350	7,4	Yanmar	PAC 2	172	379	109 x 58 x 65	18.200,00

\* With splash lubrication , Oil pump is optional.

According to directive DIN EN 12021

In case of order please specify :

- Operating pressure : 225 bar/3200 psi or 330 bar/4700 psi (standard version supplied with filling device 4-fold with 2 hose connections)
- Connection Type only for 225 bar/3200 psi : DIN or INT (YOKE) or DIN with reduction INT (YOKE). Length of all filling hoses = 1meter

In case this information is not provided, the price will be calculated with standard configuration

OPTIONAL EQUIPMENT	Price/EUR
Oil Pump Lubrication (Only for models indicated with an asterisk *)	€ 615,00
Automatic System (Auto. Cond. Drain, Autostop, Electric Start with Key)	€ 2.360,00
Oil Alert	€ 260,00
Hour meter	€ 178,00
Filtering System (PAC Filter 2)	€ 375,00
Filtering System (PAC Filter 3) Upgrade from PAC Filter 1	€ 765,00
Filtering System (PAC Filter 3) Upgrade from PAC Filter 2	€ 390,00
Double pressure (Pressure reducer with 2 ea. Filling devices 2-fold with 2 connections at 225bar/3200psi and 2 connections at 330bar/4700psi – Standard version supplied with 1 filling hose DIN 200 bar and 1 filling hose DIN 300 bar)	€ 894,00
Additional hose connections (for a maximum of 2 hose connections with pressure gauge: 225bar/3200 or 330bar/4700psi)	€ 260,00
Reduction connection DIN / INT-YOKE only for 225 bar/3200psi with connection DIN (each piece)	€ 47,00
Trolley (2 wheels and handle)	€ 455,00
Handles (Set of 2)	€ 252,00
Eco-Friendly Condensate Collecting Container/Tank 12 l.	€ 155,00
Large separators	€ 260,00

All prices are quoted in euros EX-WORKS (Incoterms ICC 2020).





**Price list**  
**HIGH PRESSURE**  
**BREATHING AIR COMPRESSOR**

**PL BREATHING HP-23**

**rev.00**

**pag. 6 di 11**

# **PACIFIC C**

**max 330 Bar / 4700 psig**



BASIC VERSION											
Model	F.A.D.		Nr. of stages	Speed Rpm	Power kW	Phase	Purification system	Weight		Dimensions L x W x H	Price EUR
	l/min	cfm						Kg	lbr		
Electric motor											
PACIFIC C 16 *	160	5,6	3	1350	3,0	single	PAC 1	234	516	75 x 93 x 123	12.595,00
PACIFIC C 23 *	230	8,1	3	1350	4,0	three	PAC 1	234	516	75 x 93 x 123	12.780,00
PACIFIC C 27 *	270	9,5	3	1550	5,5	three	PAC 1	239	527	75 x 93 x 123	13.060,00
PACIFIC C 30	300	10,6	3	1450	5,5	three	PAC 1	239	527	75 x 93 x 123	14.170,00
PACIFIC C 35	350	12,4	4	1550	7,5	three	PAC 2	247	545	75 x 93 x 123	16.440,00

\*With splash lubrication , Oil pump is optional.

**Oil alert is available as a standard feature.**

According to directive DIN EN 12021

In case of order please specify :

- Operating pressure : 225 bar/3200 psi or 330 bar/4700 psi (standard version supplied with filling device 2-fold with 2 hose connections)
- Connection Type only for 225 bar/3200 psi : DIN or INT (YOKE) or DIN with reduction INT (YOKE). Length of all filling hoses = 1meter
- Operating voltage (electric version three phase) Volt/Hz : 230/50 - 230/60 - 400/50<sup>(1)</sup> - 400/60 - 440/50 - 440/60 - 480/50 - 480/60

In case this information is not provided, the price will be calculated with standard configuration

OPTIONAL EQUIPMENT	Price EUR
Soft Start (available for PACIFIC C with charging rate 230 lpm, 270 lpm, 300 lpm and 350 lpm)	€ 1.400,00
Oil Pump Lubrication (Only for models indicated with an asterisk *)	€ 615,00
Additional Pressure Sensors (only for Electric models) (unit price per sensor)	€ 430,00
Additional Temperature Sensors (only for Electric models) (unit price per sensor)	€ 170,00
Filtering System (PAC Filter 2)	€ 375,00
Filtering System (PAC Filter 3) Upgrade from PAC Filter 1	€ 765,00
Filtering System (PAC Filter 3) Upgrade from PAC Filter 2	€ 390,00
Double pressure with safety valve (2 hose connections : n°1 225bar/3200 psi and n°1 330bar/4700psi)	€ 895,00
Reduction connection DIN / INT-YOKE only for 225 bar/3200psi with connection DIN (each piece)	€ 47,00
Eco-Friendly Condensate Collecting Container/Tank 12 l.	€ 155,00
Large separators	€ 260,00
Air quality analyzer (Co, Co <sub>2</sub> , ABS humidity, O <sub>2</sub> ) for (ABS humidity major precision sensor +1700€)	€ 1650,00
Air quality analyzer (Co, Co <sub>2</sub> , ABS humidity, O <sub>2</sub> , Oil) for (ABS humidity major precision sensor +1700€)	€ 2450,00

All prices are quoted in euros EX-WORKS (Incoterms ICC 2020).



## PACIFIC M

**max 330 Bar / 4700 psig**



BASIC VERSION											
Model	F.A.D.**		Nr. of stages	Speed rpm	Power kW	Phase	Purification system	Weight		Dimensions L x W x H	Price EUR
	l/min	cfm						Kg	lbr		
Electric motor											
PACIFIC M 23 *	230	8,1	3	1350	4,0	three	PAC 1	264	582	75 x 108 x 134	14.140,00
PACIFIC M 27 *	270	9,5	3	1550	5,5	three	PAC 1	269	593	75 x 108 x 134	14.545,00
PACIFIC M 30	300	10,6	3	1450	5,5	three	PAC 1	269	593	75 x 108 x 134	15.590,00
PACIFIC M 35	350	12,4	4	1550	7,5	three	PAC 2	277	674	75 x 108 x 134	18.165,00

\* With splash lubrication , Oil pump is optional.

**Oil alert is available as a standard feature.**

According to directive DIN EN 12021

In case of order please specify :

- Operating pressure : 225 bar/3200 psi<sup>(1)</sup> or 330 bar/4700 psi (standard version supplied with filling device 4-fold with 2 hose connections)
- Connection Type only for 225 bar/3200 psi : DIN<sup>(1)</sup> or INT (YOKE) or DIN with reduction INT (YOKE). Length of all filling hoses = 1meter
- Operating voltage (electric version three phase) Volt/Hz : 230/50 - 230/60 - 400/50<sup>(1)</sup> - 400/60 - 440/50 - 440/60 - 480/50 - 480/60

In case this information is not provided, the price will be calculated with standard configuration

OPTIONAL EQUIPMENT	Price EUR
Soft Start	€ 1.400,00
Oil Pump Lubrication (Only for models indicated with an asterisk *)	€ 615,00
Additional Pressure Sensors (only for Electric models) (unit price per sensor)	€ 430,00
Additional Temperature Sensors (only for Electric models) (unit price per sensor)	€ 170,00
Filtering System (PAC Filter 2)	€ 375,00
Filtering System (PAC Filter 3) Upgrade from PAC Filter 1	€ 765,00
Filtering System (PAC Filter 3) Upgrade from PAC Filter 2	€ 390,00
Double pressure (Pressure reducer with 2 ea. Filling devices 2-fold with 2 connections at 225bar/3200psi and 2 connections at 330bar/4700psi – Standard version supplied with 1 filling hose DIN 200 bar and 1 filling hose DIN 300 bar)	€ 895,00
Additional hose connections (for a maximum of 2 hose connections with pressure gauge: 225bar/3200 or 330bar/4700psi)	€ 260,00
Reduction connection DIN / INT-YOKE only for 225 bar/3200psi with connection DIN (each piece)	€ 47,00
Fast refill system Automatic selector By-pass + storage 100lt. with special M frame (2 tank 50lt x 300bar)	€ 7.315,00
Eco-Friendly Condensate Collecting Container/Tank 12 l.	€ 155,00
Large separators	€ 260,00
Atex Certificate Zone II	€ 4.875,00
Air quality analyzer (Co, Co <sub>2</sub> , ABS humidity, O <sub>2</sub> ) for (ABS humidity major precision sensor +1700€)	€ 1650,00
Air quality analyzer (Co, Co <sub>2</sub> , ABS humidity, O <sub>2</sub> , Oil) for (ABS humidity major precision sensor +1700€)	€ 2450,00

All prices are quoted in euros EX-WORKS (Incoterms ICC 2020).



## PACIFIC M NITROX

**max 330 Bar / 4700 psig**

**4 stages**



BASIC VERSION										
Model	F.A.D.		Speed	Power	Pump unit	Purification	Weight		Dimensions	Price
	l/min	cfm	rpm	kW		system	Kg	lbr	L x W x H	EUR
Electric motor										
PACIFIC M NITROX 30	300	10,6	1300	5,5	PAC35	PAC 2	277	674	75 x 108 x 134	19.980,00

**Pressure and Temperature Sensors on all stages are a standard feature.**

According to directive DIN EN 12021

In case of order please specify :

- Operating pressure : 225 bar/3200 psi (standard version supplied with filling device 4-fold with 2 hose connections)
- Connection Type only for 225 bar/3200 psi : DIN or INT (YOKE) or DIN with reduction INT (YOKE). Length of all filling hoses = 1meter
- Operating voltage (electric version three phase) Volt/Hz : 230/50 - 230/60 - 400/50 - 400/60 - 440/50 - 440/60 - 480/50 - 480/60

In case this information is not provided, the price will be calculated with standard configuration

OPTIONAL EQUIPMENT	Price EUR
Soft Start	€ 1.400,00
Filtering System (PAC Filter 3) Upgrade from PAC Filter 2	€ 390,00
Double pressure (Pressure reducer with 2 ea. Filling devices 2-fold with 2 connections at 225bar/3200psi and 2 connections at 330bar/4700psi – Standard version supplied with 1 filling hose DIN 200 bar and 1 filling hose DIN 300 bar)	€ 895,00
Additional hose connections (for a maximum of 2 hose connections with pressure gauge: 225bar/3200 or 330bar/4700psi)	€ 290,00
Reduction connection DIN / INT-YOKE only for 225 bar/3200psi with connection DIN (each piece)	€ 47,00
Eco-Friendly Condensate Collecting Container/Tank 12 l.	€ 155,00
Air quality analyzer (Co, Co <sub>2</sub> , ABS humidity, O <sub>2</sub> ) for (ABS humidity major precision sensor +1700€)	€ 1650,00
Air quality analyzer (Co, Co <sub>2</sub> , ABS humidity, O <sub>2</sub> , Oil) for (ABS humidity major precision sensor +1700€)	€ 2450,00

All prices are quoted in euros EX-WORKS (Incoterms ICC 2020).



## PACIFIC CX

max 330 Bar / 4700 psig



BASIC VERSION											
Model	F.A.D.**		Nr. of stages	Speed rpm	Power kW	Phase	Purification System	Weight		Dimensions L x W x H	Price EUR
	l/min	m3/h						Kg	lbr		
PACIFIC MX Silenced Version											
PACIFIC MX 50	500	30	3	1100	11	three	PAC 3	400	1014		18.700,00
PACIFIC MX 60	600	36	3	1300	11	three	Double PAC3	420			21.150,00
PACIFIC MX 68	680	42	4	1100	15	three	Double PAC3	470	1146		26.400,00
PACIFIC MX 85	850	51	4	1300	18.5	three	Double PAC3	570	1367		29.400,00

**Soft Start, Oil Pump, Oil Alert and Large separators are available as standard features on all PACIFIC MX compressors.**

According to directive DIN EN 12021

In case of order please specify :

- Operating pressure : 225 bar/3200 psi or 330 bar/4700 psi (standard version supplied with filling device 4-fold with 4 hose connections)
- Connection Type only for 225 bar/3200 psi : DIN or INT (YOKE) or DIN with reduction INT (YOKE). Length of all filling hoses = 1meter
- Operating voltage (electric motor three phase) Volt/Hz : 230/50 - 230/60 - 400/50 - 400/60 - 440/50 - 440/60 - 480/50 - 480/60

(1) In case this information is not provided, the price will be calculated with standard configuration

(2) All compressors of PACIFIC MX range are equipped with four n. 4 filling hoses and Eco-friendly condensate collecting Container 12 Lt.

OPTIONAL EQUIPMENT	Price EUR
Additional Pressure Sensors (only for Electric models) (unit price per sensor)	€ 430,00
Additional Temperature Sensors (only for Electric models) (unit price per sensor)	€ 170,00
Supplementary Filtering System (2 x PAC Filter 3) Upgrade from single PAC Filter 3 for MX 48 and MX 60	€ 1.950,00
Double pressure (Pressure reducer with 2 ea. Filling devices 2-fold with 2 connections at 225bar/3200psi and 2 connections at 330bar/4700psi – Standard version supplied with 2 filling hoses DIN 200 bar and 2 filling hoses DIN 300 bar)	€ 895,00
Reduction connection DIN / INT-YOKE only for 225 bar/3200psi with connection DIN (each piece)	€ 47,00
Fast refill system Automatic selector By-pass +storage 100 Lt with special MX frame (2 tank 50lt x 300bar)	€ 8.500,00
600 Lt Air Storage with Bundle of 12 cylinders of 50 lt each @ 300 Bar (PA011-010)	€ 20.600,00
800 Lt Air Storage with Bundle of 16 cylinders of 50 lt each @ 300 Bar (PA011-013)	€ 27.500,00
Atex Certificate Zone II	€ 4.875,00
Air quality analyzer (Co, Co <sub>2</sub> , ABS humidity, O <sub>2</sub> ) for (ABS humidity major precision sensor +1700€)	€ 1650,00
Air quality analyzer (Co, Co <sub>2</sub> , ABS humidity, O <sub>2</sub> , Oil) for (ABS humidity major precision sensor +1700€)	€ 2450,00

All prices are quoted in euros EX-WORKS (Incoterms ICC 2020).



**Price list**  
**HIGH PRESSURE**  
**BREATHING AIR COMPRESSOR**

**PL BREATHING HP-23**

**rev.00**

**pag. 10 di 11**

## **PACIFIC MX**

**max 330 Bar / 4700 psig**



BASIC VERSION											
Model	F.A.D.**		Nr. of stages	Speed rpm	Power kW	Phase	Purification System	Weight		Dimensions L x W x H	Price EUR
	l/min	m3/h						Kg	lbr		
PACIFIC MX Silenced Version											
PACIFIC MX 50	500	30	3	1100	11	three	PAC 3	460	1014	87x156x173	20.550,00
PACIFIC MX 60	600	36	3	1300	11	three	Double PAC3	500		87x156x173	22.900,00
PACIFIC MX 60/4	600	36	4	950	11	three	Double PAC3	520		87x156x173	27.300,00
PACIFIC MX 68	680	42	4	1100	15	three	Double PAC3	520	1146	87x156x173	28.100,00
PACIFIC MX 85	850	51	4	1300	18.5	three	Double PAC3	620	1367	87x156x173	31.050,00

**Soft Start, Oil Pump, Oil Alert and Large separators are available as standard features on all PACIFIC MX compressors.**

According to directive DIN EN 12021

In case of order please specify :

- Operating pressure : 225 bar/3200 psi or 330 bar/4700 psi (standard version supplied with filling device 4-fold with 4 hose connections)
- Connection Type only for 225 bar/3200 psi : DIN or INT (YOKE) or DIN with reduction INT (YOKE). Length of all filling hoses = 1meter
- Operating voltage (electric motor three phase) Volt/Hz : 230/50 - 230/60 - 400/50 - 400/60 - 440/50 - 440/60 - 480/50 - 480/60

(3) In case this information is not provided, the price will be calculated with standard configuration

(4) All compressors of PACIFIC MX range are equipped with four n. 4 filling hoses and Eco-friendly condensate collecting Container 12 Lt.

OPTIONAL EQUIPMENT		Price EUR
Additional Pressure Sensors (only for Electric models) (unit price per sensor)		€ 430,00
Additional Temperature Sensors (only for Electric models) (unit price per sensor)		€ 170,00
Supplementary Filtering System (2 x PAC Filter 3) Upgrade from single PAC Filter 3 for MX 48 and MX 60		€ 1.950,00
Double pressure (Pressure reducer with 2 ea. Filling devices 2-fold with 2 connections at 225bar/3200psi and 2 connections at 330bar/4700psi – Standard version supplied with 2 filling hoses DIN 200 bar and 2 filling hoses DIN 300 bar)		€ 895,00
Reduction connection DIN / INT-YOKE only for 225 bar/3200psi with connection DIN (each piece)		€ 47,00
Fast refill system Automatic selector By-pass +storage 100 Lt with special MX frame (2 tank 50lt x 300bar)		€ 8.500,00
600 Lt Air Storage with Bundle of 12 cylinders of 50 lt each @ 300 Bar (PA011-010)		€ 20.600,00
800 Lt Air Storage with Bundle of 16 cylinders of 50 lt each @ 300 Bar (PA011-013)		€ 27.500,00
Atex Certificate Zone II		€ 4.875,00
Air quality analyzer (Co, Co <sub>2</sub> , ABS humidity, O <sub>2</sub> ) for (ABS humidity major precision sensor +1700€)		€ 1650,00
Air quality analyzer (Co, Co <sub>2</sub> , ABS humidity, O <sub>2</sub> , Oil) for (ABS humidity major precision sensor +1700€)		€ 2450,00

All prices are quoted in euros EX-WORKS (Incoterms ICC 2020).



## **PACIFIC MX NITROX**

**max 330 Bar / 4700 psig**

**4 stages**



BASIC VERSION										
Model *	F.A.D.**		Speed	Power	Pump unit	Purification System	Weight		Dimensions	Price
	l/min	m3/h	rpm	kW			Kg	lbr		
PACIFIC MX NITROX Silenced Version										
PACIFIC MX 60N	600	36	950	11	MX 60	2 x PAC 3	520	1146	87 x 156 x 173	29.100,00

**Soft Start, Oil Pump, Oil Alert, Large separators and Temperature and Pressure Sensors on all stages are available as standard features.**

According to directive DIN EN 12021

In case of order please specify :

- Operating pressure : 225 bar/3200 psi (standard version supplied with filling device 4-fold with 4 hose connections)
- Connection Type only for 225 bar/3200 psi : DIN or INT (YOKE) or DIN with reduction INT (YOKE). Length of all filling hoses = 1meter
- Operating voltage (electric motor three phase) Volt/Hz : 230/50 - 230/60 - 400/50 - 400/60 - 440/50 - 440/60 - 480/50 - 480/60
  - (1) In case this information is not provided, the price will be calculated with standard configuration
  - (2) All compressors of PACIFIC MX range are equipped with four n. 4 filling hoses and Eco-friendly condensate collecting Container 12 Lt.

OPTIONAL EQUIPMENT	Price EUR
Double pressure (Pressure reducer with 2 ea. Filling devices 2-fold with 2 connections at 225bar/3200psi and 2 connections at 330bar/4700psi – Standard version supplied with 2 filling hoses DIN 200 bar and 2 filling hoses DIN 300 bar)	€ 895,00
Air quality analyzer (Co, Co <sub>2</sub> , ABS humidity, O <sub>2</sub> ) for (ABS humidity major precision sensor +1700€)	€ 1650,00
Air quality analyzer (Co, Co <sub>2</sub> , ABS humidity, O <sub>2</sub> , Oil) for (ABS humidity major precision sensor +1700€)	€ 2450,00

All prices are quoted in euros EX-WORKS (Incoterms ICC 2020).